



111 Merchants St. - San Antonio, TX 78204  
 Tel: (210) 226-8271 Fax: (210) 226-0913



## BULLET-RESISTING EQUIPMENT RATINGS UL-752 SPECIFICATIONS

Rating	Ammunition	Weight		Minimum Velocity		Number of shots
		Grains	(grams)	fps	(m/s)	
Level 1	9 mm full metal copper jacket with lead core	124	8.0	1,175	358	3
Level 2	.357 Magnum jacketed lead soft point	158	10.2	1,250	381	3
Level 3	.44 Magnum lead semi-wadcutter gas checked	240	15.6	1,350	411	3
Level 4	.30 caliber rifle lead core soft point	180	11.7	2,540	774	1
Level 5	7.62 mm rifle lead core full metal copper jacket, military ball	150	9.7	2,750	838	1
Level 6	9 mm full metal copper jacket with lead core	124	8.0	1,400	427	5
Level 7	5.56 mm rifle full metal copper jacket with lead core	55	3.56	3,080	939	5
Level 8	7.62 mm rifle lead core full metal copper jacket, military ball	150	9.7	2,750	838	5
* Level 9	Armor piercing .30 caliber rifle, steel core lead point filler, full metal jacket	166	10.8	2,715	828	1
* Level 10	.50 caliber rifle, lead core full metal copper jacket, military ball	709.5	45.9	2810	856	1
Supp. Shotgun	12-Gauge rifled lead slug	437	28.3	1,585	483	3
Supp. Shotgun	12-Gauge 00 lead buckshot (12 pellets)	650	42	1,200	366	3

Note: Maximum velocity is one hundred ten percent, 110%, of the minimum velocity.

\* Proposed levels